

Technical Data Sheet



Artical- No : KS 009 –COTTON CANVAS MAT
 Treatment applied for Sol, Eco Sol, Latex, Uv-Curable

Material : 100 % Cotton

Stock widths : app. 102cm, 152 cm, 306 cm

Finishing : rolled on paper cores

Packaging : wrapped with foil + put in a cardboard box

Ecology : according to Öko-Tex Standard 100

Weight

Acc. To DIN EN 12127 290.0 (g/ m2) +- 5 (gr)

Shrinkage :

Heat Shrinkage , 210 OC, 110 sec , lengthwise -1.3 (%) +- 0.2 (%)
 Acc. To AA 25-02

Heat Shrinkage , 210 OC, 110 sec , crosswise -0.9 (%) +- 0.2 (%)
 Acc. to AA 25-02

Tensile Strength

Strain at Peak

Maximum tensile elongation, weft direction 11.90 (%) CV(%): 4,4
 acc. to DIN EN ISO 13934-1

Maximum tensile elongation, warp direction 14.00 (%) CV(%): 1,9
 acc. to DIN EN ISO 13934-1

Maximum Force

Maximum tensile elongation, weft direction min. 590.00 (N/5 cm) CV(%): 3,1
 acc. to DIN EN ISO 13934-1

Maximum tensile elongation, warp direction min. 1100.00 (N/5 cm) CV(%): 0,9
 acc. to DIN EN ISO 13934-1

Tear Strength

Maximum tear elongation, weft direction min. 12 (N) CV(%): 2,8
 acc. to DIN EN ISO 13937-1

Maximum tear elongation, warp direction min. 16 (N) CV(%): 0,9
 acc. to DIN EN ISO 13937-1